

Radio Frequency

IRDA/RS232



Print from
PalmOS and
PocketPC2002

Long Lasting

Light Weight

Thermal Portable Printers

s'print

s'print

s'print portable thermal printers offer an innovative alternative to impact-based systems.

Very light weight and compact size. Easy paper automatic loading through the "sixload" patented system. End of paper and black mark sensors. Updating customer logo and most common barcodes printing: EAN 13, EAN 8, CODE 39, ITF, CODABAR.

s'print-s is powered using an **external power supply**, with RS232 serial interface.

The printer is suitable for applications such as instruments, receipts and coupon printing, bank transactions confirming reports.

s'print-b is powered using **batteries** with RS232 serial interface + Bidirectional infrared.

s'print-i is powered using **batteries** with RS232 serial interface+IrDA (IrDA protocol supported: IrLPT/IrCOMM 3 wire raw).

s'print-BT is able to print wireless at high speed without any alignment thanks to radio frequency wireless technology.

It is powered by **batteries** with RS232 serial interface + Bluetooth™. The supported profiles are SPP (Serial Port Profile) that provides RS232 serial cable emulation, and OPP (Object Push Profile) enabling the print-out of vCard format objects (business cards).

s'print-b, s'print-i and s'print-BT are suitable for "wireless" applications, combined with PDAs, laptop computers and mobile phones.

s'print-LP1 printer for labels, width 58mm and height 1" inch minimum. s'print-LP1 finds ideal application in automatic identification and safety markets, in automotive and combined with portable terminals without printers. It is equipped with EasyLabel software to create/manage labels (Windows 98/2k/XP).

Print from PDAs

With s'print-i is possible to print text and graphic from all Palm Powered products thanks to PalmOSprint free application.

It's also available on request a libraries set to allow printing application development.

PalmOS and Microsoft PocketPC2002 (Windows CE compatible) are the supported platforms.

Batteries

Battery charger: 12-36 VDC/0.6A.
Batteries: 5 AA penlight (NI-MH/NI-CD/ALKALINE).
Battery Life: 140 mt. of paper (STANDARD CUSTOM receipt and 1850 mAh battery).
Autonomy (hours): 2 h 20 min (STANDARD CUSTOM receipt and 1850 mAh battery).

Accessories

s'print is equipped with a handy belt fixing hook and a smart and tough shock resistant holder.



s'print
Your Smaller
Portable Printer



s'print - BT /LP1

Printing Method	Thermal line printing
Resolution	203 dpi
Printing Speed	> 50 mm/sec (It depends by the battery status, the printing typology and the environment temperature.)
Columns	24 (40/42 version is available)
Character Set	ASCII standard, International
Type Styles	Normal, double height/width, negative, underlines, expanded
Printing Direction	Straight, reverse
Paper Width	58 mm
Roll Dimension	57.5 mm ± 1mm
Emulation	Custom
Interface	RS232 + Bluetooth™ (power class: 3, max distance: 10 mt)
IRDA protocol	
Supported Bluetooth™ profiles	SPP (Serial Port Profile) & OPP (Object Push Profile)
Baud Rate	600 to 38.400 bps
Data Buffer	128 byte
Flash Memory	32K
Graphic Memory	1 logo of 384 x 85 dot
Drivers	Windows™ 95 / 98 / me / NT4 / 2K / XP
Software Tools	LogoEditor, FontEditor, Easy Label, 40/42 columns font available
Power	12-36 Vdc / 0.6A (battery charger)
Power Consumption	925 mA
Reliability MTBF	50 Km
Safety	EN60950+A1+A2+A3+A4
Dimension	146 x 88 x 65 mm
Weight	370 gr (without paper roll)



VIC COMPUTER (HK) CO., LTD.
域士電腦(香港)有限公司
Tel: (852) 2725 1612
Fax: (852) 2725 0766
email: Sales@VIC.HK
http://VIC.HK